

# FTXA-A/B (W/S/T/B) / RXA-A/B

**R-32** BLUEEVOLUTION

Indoor Units	White	CTXA15AW	FTXA20AW	FTXA25AW	FTXA35AW	FTXA42AW	FTXA50AW	
	Black	CTXA15BB	FTXA20BB	FTXA25BB	FTXA35BB	FTXA42BB	FTXA50BB	
	Silver	CTXA15BS	FTXA20BS	FTXA25BS	FTXA35BS	FTXA42BS	FTXA50BS	
	Blackwood	CTXA15BT	FTXA20BT	FTXA25BT	FTXA35BT	FTXA42BT	FTXA50BT	
Capacity	UK Total Cooling	Multi Combination Only		1.95	2.44	3.32	4.11	4.89
	UK Sensible Cooling		1.95	1.96	2.43	3.01	3.56	
	Nominal Cooling		2.0	2.5	3.4	4.2	5.0	
	Nominal Heating		2.5	2.8	4.0	5.4	5.8	
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+++	A+++	A+++	A++	A++	
	Pdesign		2.0	2.5	3.4	4.2	5.0	
	SEER		8.75	8.74	8.73	7.50	7.39	
	Annual Energy Consumption		80	101	137	196	239	
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+++	A+++	A+++	A++	A++	
	Pdesign		2.40	2.45	2.50	3.80	4.00	
	SCOP		5.15	5.15	5.15	4.6	4.6	
	Annual Energy Consumption		653	666	680	1156	1217	
Nominal Efficiency	EER/COP		4.70/6.27	4.46/6.25	4.37/6.19	3.99/6.33	3.68/6.32	
Air Flow Rate (Cooling)	High / Nom / Low / Silent	m <sup>3</sup> /sec	0.183/0.136/0.101/ 0.076	0.183/0.136/0.101/ 0.076	0.191/0.143/0.101/ 0.076	0.198/0.143/0.101/ 0.076	0.218/0.163/0.120/ 0.076	0.225/0.173/0.126/ 0.086
Dimensions	Height / Weight / Depth	mm	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	
Weight		kg	12	12	12	12	12	
Sound Pressure (Cooling)	High / Nom / Low / Silent	dB(A)	39/32/25/21	39/32/25/19	40/33/25/19	41/33/25/19	45/37/29/21	46/39/31/24
Sound Power (Cooling)		dB(A)	57	57	57	60	60	
Outdoor Units			RXA20A	RXA25A	RXA35A	RXA42B	RXA50B	
Dimensions	Height x Width x Depth	mm	550 x 765 x 285	550 x 765 x 285	550 x 765 x 285	734 x 870 x 373	734 x 870 x 373	
Weight		kg	32	32	32	50	50	
Electrical Details	Power Supply		1ph	1ph	1ph	1ph	1ph	
	Running Current	A	-	-	-	-	-	
	Starting Current	A	-	-	-	-	-	
	Max Fuse Size	A	10	13	13	13	13	
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)	
Pipework	Maximum Length	m	20	20	20	30	30	
	Maximum Vertical Rise	m	15	15	15	20	20	
	Precharged to	m	10	10	10	10	10	
	Additional charge	g/m	20	20	20	20	20	
	Holding charge	kg	0.76	0.76	0.76	1.1	1.1	
Sound Pressure (Cooling)	High	dB(A)	46	46	49	48	48	
Sound Power (Cooling)		dB(A)	59	59	61	62	62	
Operating Range (Cooling)	Min / Max	°CDB	-10/46	-10/46	-10/46	-10/46	-10/46	
Operating Range (Heating)	Min / Max	°CWB	-15/18	-15/18	-15/18	-15/18	-15/18	
ECA Eligible			•	•	•	•	•	

## Accessories:

Accessory Ref	Description
EKR521	Wire harness for new S21 port for all marked (*) options
BRC073*	Optional wired remote controller BRC1E53 style - Connection cable required
BRCW901A03	3m connection cable for BRC073
BRCW901A08	8m connection cable for BRC073
K.CGM	Condensing unit guard size Split 42-71/ Sky Air 35-250
K.CGS	Condensing unit guard size 20-35
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with K.CWB90-2
KLIC-DD*	KNX interface for Split type systems
KRP413A1S*	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A2S*	Adaptor PCB for interface to Daikin centralised control systems

## Notes & Features:

- > All fan coils are supplied with infrared remote controller ARC466A58
- > New fan with Coanda effect for optimum air distribution and indoor comfort
- > New grid eye sensor redirects air away from the occupants in the room
- > Flash Streamer helps improving the indoor air quality

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)