

GV19 Ø 197 mm



Code	Type	60Hz Available	Idraulic P. P2 - kW	Nom.I A	Thrust N	Weight Kg
6007801	GV19B409T1-4T6KA0	Yes	1,4	3,2	275	40
<i>Con anello convogliatore - With jet ring - Concentrateur de flux Mit Strömungsring - Anillo de chorro - Com condutor</i>						
6008789	GV19B409T1-4C6KA0	-	1	2,6	220	43

Motor	Power supply	Rot.speed R.P.M.	P2 kW	Max.I A	Is A	Cosφ
M409T/LR-IE1/3,0	3ph 400V 50Hz	1350	2,4	4,9	22,1	0,89



Versione Disponibile - Type Available - Version Disponible
Vorhanden - Displonible - Versão disponível

GV30A Ø 300 mm



Code	Type	60Hz Available	Idraulic P. P2 - kW	Nom.I A	Thrust N	Weight Kg
6001521	GV30A609T1-4T6KA0	Yes	1,5	4,6	300	44
<i>Con anello convogliatore - With jet ring - Concentrateur de flux Mit Strömungsring - Anillo de chorro - Com condutor</i>						
6008813	GV30A609T1-4C6KA0	-	1,0	3,8	240	47

Motor	Power supply	Rot.speed R.P.M.	P2 kW	Max.I A	Is A	Cosφ
M609T/L	3ph 400V 50Hz	930	2,3	6	24,6	0,79



Versione Disponibile - Type Available - Version Disponible
Vorhanden - Displonible - Versão disponível

GV30B Ø 300 mm



Code	Type	60Hz Available	Idraulic P. P2 - kW	Nom.I A	Thrust N	Weight Kg
6001522	GV30B610R1-4T6KA2	Yes	1,9	5,5	320	57
<i>Con anello convogliatore - With jet ring - Concentrateur de flux Mit Strömungsring - Anillo de chorro - Com condutor</i>						
6008814	GV30B610R1-4C6KA2	-	1,3	4,2	280	60

Motor	Power supply	Rot.speed R.P.M.	P2 kW	Max.I A	Is A	Cosφ
M610T/MR-IE0/3,6	3ph 400/690V 50Hz	890	2,8	6,6	31	0,79



Versione Disponibile - Type Available - Version Disponible
Vorhanden - Displonible - Versão disponível