

GV37 Ø 370 mm



Code	Type	60Hz Available	Idraulic P. P2 - kW	Nom.I A	Thrust N	Weight Kg
6009060	GV37B810R1-4T6KA2	Yes	1,1	3,0	385	58
<i>Con anello convogliatore - With jet ring - Concentrateur de flux Mit Strömungsring - Anillo de chorro - Com condutor</i>						
6007570	GV37B810R1-4C6KA2	-	1	2,6	320	70

Motor	Power supply	Rot.speed R.P.M.	P2 kW	Max.I A	Is A	Cosφ
M810T/M	3ph 400/690V 50Hz	690	1,3	4,0	13,6	0,74



Versione Disponibile - Type Available - Version Disponible
Vorhanden - Disponible - Versão disponível

GV40₁₋₂ Ø 400 mm



Code	Type	60Hz Available	Idraulic P. P2 - kW	Nom.I A	Thrust N	Weight Kg
6001519	GV40B813R1-4T6KA2	Yes	1,7	5,5	420	114
6002688	GV40B813R2-4T6KA2	Yes	2,5	6,8	650	114
<i>Con anello convogliatore - With jet ring - Concentrateur de flux Mit Strömungsring - Anillo de chorro - Com condutor</i>						
6004997	GV40B813R1-4C6KA2	-	1,4	4,8	360	120
6006303	GV40B813R2-4C6KA2	-	1,8	5,4	560	120

Motor	Power supply	Rot.speed R.P.M.	P2 kW	Max.I A	Is A	Cosφ
M813T/MR	3ph 400/690V 50Hz	670	3,7	8,7	29,6	0,8

GV40₃ Ø 400 mm



Code	Type	60Hz Available	Idraulic P. P2 - kW	Nom.I A	Thrust N	Weight Kg
6008654	GV40B813R3-4T6SA2	Yes	3,4	8,4	780	125
<i>Con anello convogliatore - With jet ring - Concentrateur de flux Mit Strömungsring - Anillo de chorro - Com condutor</i>						
6009229	GV40B813R3-4C6SA2	-	2,6	6,6	680	130

Motor	Power supply	Rot.speed R.P.M.	P2 kW	Max.I A	Is A	Cosφ
M813T/Lp	3ph 400/690V 50Hz	710	5,8	14,5	39,2	0,72