




Disegno Drawing Чертеж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы			Pressione differenziale d'apertura Opening differential pressure [bar] Открытие перепад давления [бар]	Kv [m³/h] Kv [m³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare раз- вальц SAE	ODS [in.]/ [дюйм]	ODS [mm]				min мин	max макс	
	3136W/M12	N	-	-	1,4 - 3	1,5	45	- 40	+ 110	16
	3136W/4	N	-	1/2"						

Valvole 3136/.. in esaurimento scorte  
Valves 3136/.. running out of stock  
Клапаны 3136/.. заканчиваются на складе

REGOLATORI DI PRESSIONE DEL RICEVITORE - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.  
RECEIVER PRESSURE REGULATORS - APPROVED BY UNDERWRITERS LABORATORIES INC.  
РЕГУЛЯТОРЫ ДАВЛЕНИЯ В РЕСИВЕРЕ, УТВЕРЖДЕННЫЕ UNDERWRITERS LABORATORIES INC.

Disegno Drawing Чертеж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы			Campo di regolazione Regulation range [bar] Диапазон регулирования давления [бар]	Kv [m³/h] Kv [m³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare раз- вальц SAE	ODS [in.]/ [дюйм]	ODS [mm]				min мин	max макс	
	3350/4	1/2"	-	-	3 - 20	1,8	28 (1)	- 40	+ 110	15
	3350/5	5/8"	-	-						15
	3350/M12S	-	-	12	3-20	1,8	28 (1)	- 40	+ 110	15
	3350/4S	-	1/2"	-						15
	3350/5S	-	5/8"	16						15

Note:  
(1): MWP = 405 psi in conformità a omologazione UL  
(1): MWP = 405 psi according to UL approval  
Примечание.  
(1): Максимальное рабочее давление = 405 psi соответствует значению, одобренному UL.