

# ATXP-M + ARXP-M




Efficiency data		ATXP + ARXP	20M + 20M	25M + 25M	35M + 35M	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	
Power input	Cooling	Min./Nom./Max.	0.31/0.50/0.72	0.31/0.66/0.72	0.29/1.01/1.30	
	Heating	Min./Nom./Max.	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	
Space cooling	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.00	2.50	3.50
	SEER			6.77	6.85	6.56
	Annual energy consumption		kWh/a	104	128	187
Space heating (Average climate)	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.20	2.40	2.80
	SCOP/A			4.64	4.60	4.62
	Annual energy consumption		kWh/a	663	730	847
Nominal efficiency	EER			3.98	3.79	3.45
	COP			4.77	4.36	4.02
	Energy labeling Directive	Cooling/Heating		A/A		

Indoor unit		ATXP	20M	25M	35M		
Dimensions	Unit HeightxWidthxDepth	mm	286x770x225				
Weight	Unit	kg	8.50		9.00		
Air filter	Type		Removable / washable				
Fan	Air flow	Cooling	Silent operation/Low/Medium/High	m <sup>3</sup> /min	4.2/5.6/7.4/9.5	4.2/5.8/7.7/9.7	4.5/6.3/8.3/11.5
	rate	Heating	Silent operation/Low/Medium/High	m <sup>3</sup> /min	5.2/6.2/8.1/10.4	5.2/6.4/8.1/10.4	5.3/7.0/9.0/11.5
Sound power level	Cooling			55		58	
	Heating			55		58	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	19/25/39	19/26/40	20/27/43	
	Heating	Silent operation/Low/High	dBA	21/28/39	21/28/40	21/29/40	
Control systems	Infrared remote control		ARC480A53				
	Wired remote control		BRC944B2 / BRC073A1				
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240				

Outdoor unit		ARXP	20M	25M	35M	
Dimensions	Unit HeightxWidthxDepth	mm	550x658x275			
Weight	Unit	kg	26		28	
Sound power level	Cooling			60		62
	Heating			61		62
Sound pressure level	Cooling	High	dBA	46		48
	Heating	High	dBA	47		48
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10~46
	Heating	Ambient	Min.~Max.	°CWB		-15~18
Refrigerant	Type		R-32			
	GWP		675.0			
Piping connections	Charge		kg/TCO2Eq	0.55/0.37		0.70/0.48
	Liquid	OD	mm	635		
	Gas	OD	mm	9.5		
	Piping length	OU - IU	Max.	m		
	Additional refrigerant charge			kg/m		
	Level difference	IU - OU	Max.	m		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			
Current - 50Hz	Maximum fuse amps (MFA)	A	-			

Daikin Europe N.V. Naamloze Venootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN19-047

03/2019

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

