

Model : ASHA012GCEH / ASHA014GCEH
 ASHE012GCEH / ASHE014GCEH



Specifications

| Model name | | ASHA012GCEH | ASHA014GCEH | ASHE012GCEH | ASHE014GCEH |
|---------------------------------|----------------|---------------------------|------------------|-----------------|---------------------------|
| Power source | | Single phase, ~230V, 50Hz | | | Single phase, ~230V, 50Hz |
| Capacity | Cooling | 3.6 | 4.0 | 3.6 | 4.0 |
| | Heating | 4.0 | 4.5 | 4.0 | 4.5 |
| Input power | | 25 | 36 | 25 | 36 |
| Airflow rate | High | 690 | 800 | 690 | 800 |
| | Med-H | 610 | 740 | 610 | 740 |
| | Med | 560 | 680 | 560 | 680 |
| | Med-L | 530 | 610 | 530 | 610 |
| | Low | 470 | 550 | 470 | 550 |
| | Quiet | 330 | 330 | 330 | 330 |
| Sound pressure level | High | 40 | 44 | 40 | 44 |
| | Med-H | 37 | 42 | 37 | 42 |
| | Med | 35 | 40 | 35 | 40 |
| | Med-L | 33 | 37 | 33 | 37 |
| | Quiet | 30 | 34 | 30 | 34 |
| Net Dimensions (H × W × D) | | mm | 268 × 840 × 203 | 268 × 840 × 203 | 268 × 840 × 203 |
| Weight | | kg(lbs) | 8.5 (19) | 8.5 (19) | 8.5 (19) |
| Connection pipe diameter | Liquid (Flare) | mm | 6.35 | 6.35 | 6.35 |
| | Gas (Flare) | mm | 12.70 | 12.70 | 12.70 |
| Drain hose diameter (I.D./O.D.) | | | 13.8/15.8 to16.7 | | 13.8/15.8 to16.7 |
| EV Kit (option) | | | - | | UTR-EV14XB |

Note : Specifications are based on the following conditions.
 Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].

Optional parts

External Power Supply Unit : UTZ-GXXA
 Wireless LAN Interface : UTY-TFSXZ1

Dimensions

(Unit : mm)

