

**Model: ASHG07KETA / ASHG09KETA / ASHG12KETA / ASHG14KETA
ASHG07KETA-B / ASHG09KETA-B / ASHG12KETA-B / ASHG14KETA-B**



Peal white X White



Silver X Dark gray



Wireless R.C.



For ASHG07/09/12KETA
ASHG07/09/12KETA-B



For ASHG14KETA
ASHG14KETA-B

Specifications

Model No.	Indoor unit		ASHG07KETA ASHG07KETA-B	ASHG09KETA ASHG09KETA-B	ASHG12KETA ASHG12KETA-B	ASHG14KETA ASHG14KETA-B
	Outdoor unit		AOHG07KETA	AOHG09KETA	AOHG12KETA	AOHG14KETA
Power Source			Single phase, ~230V, 50Hz			
Capacity	Cooling	kW	2.0 (0.9 - 3.0)	2.5 (0.9 - 3.2)	3.4 (0.9 - 3.9)	4.2 (0.9 - 4.4)
	Heating		2.5 (0.9 - 3.4)	2.8 (0.9 - 4.0)	4.0 (0.9 - 5.3)	5.4 (0.9 - 6.0)
Input Power	Cooling/Heating	kW	0.450 / 0.555	0.630 / 0.620	0.935 / 0.960	1.220 / 1.410
EER	Cooling	W/W	4.43	3.97	3.65	3.44
COP	Heating		4.52	4.52	4.17	3.83
Pdesign	Cooling/Heating (-10°C)	kW	2.0 / 2.3	2.5 / 2.4	3.4 / 2.5	4.2 / 4.0
SEER	Cooling	W/W	7.40	7.40	7.30	6.9
SCOP	Heating (Average)		4.10	4.10	4.40	4.1
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+
Max. Operating Current	Cooling/Heating	A	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0
Annual Energy Consumption	Cooling	kWh/a	95	118	163	213
	Heating		785	819	795	1,367
Moisture Removal		l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38 / 33 / 29 / 20	40 / 34 / 29 / 20	40 / 35 / 30 / 20	43 / 36 / 30 / 20
	Indoor (Heating)	H/M/L/Q	41 / 35 / 31 / 22	42 / 36 / 31 / 22	42 / 38 / 33 / 22	44 / 39 / 33 / 24
Sound Power Level	Outdoor (Cooling/Heating)	High	46 / 46	46 / 46	50 / 50	50 / 50
	Indoor (Cooling/Heating)	High	54 / 56	55 / 57	55 / 58	57 / 59
Airflow Rate	Indoor / Outdoor (Cooling)	High	650 / 1,650	700 / 1,650	700 / 1,700	770 / 1,680
	Indoor / Outdoor (Heating)	High	720 / 1,450	750 / 1,450	770 / 1,470	800 / 1,580
Net Dimensions H x W x D	Indoor	mm	295×950 (wall side : 840)×230			
	Outdoor	mm	541×663×290	541×663×290	541×663×290	542×799×290
Weight	Indoor	kg(lbs)	11(24)	11(24)	11(24)	11.5(25)
	Outdoor	kg(lbs)	23(51)	23(51)	25(55)	31(68)
Connection Pipe Diameter (Liquid / Gas)		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain hose Diameter (I.D./O.D.)		mm	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8
Max Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)
Max Height Difference			15	15	15	15
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg(CO2eq-T)	0.6 (0.405)	0.6 (0.405)	0.7 (0.473)	0.85 (0.574)

Optional parts

Compact Wired Remote Controller:	UTY-RCRGZ1	Communication Kit:	UTY-TWRXZ2	Network Converter for single split (DC power supply type):	UTY-VTGX
Wired Remote Controller (Touch Panel):	UTY-RNRGZ3	External input and output PCB:	UTY-XCSXZ2	Network Converter for single split (AC power supply type):	UTY-VTGXV
Wired Remote Controller:	UTY-RLRG	External Connect Kit:	UTY-XWZXZ5	KNX® Converter:	UTY-VKXSX*
Simple Remote Controller (Without operation mode):	UTY-RHRG	External Switch Controller:	UTY-TERX	MODBUS® Converter:	UTY-VMSX*
Simple Remote Controller:	UTY-RSRG	Wireless LAN Interface:	UTY-TFSXF2		

*: It can be used only when the wireless LAN interface (UTY-TFSXF2) is removed.

Dimensions

(Unit : mm)

