


DATA SHEET

EM 200 E2M 01 | 127249

ruck.eu
VENTILATOREN



- Diagonal impeller with stator
- With Plastic housing
- 3-step
- Integrated thermostatic switch
- Including mounting bracket

Operating Point		1	2	3	4	5
Current I	A	0,5	0,4	0,5	0,6	0,5
Power Consumption P _l	W	94	88	108	117	108
RPM n	1/min	2820	2851	2740	2707	2757
SPL inlet L _{WA5}	dB(A)	72	70	72	72	73
SPL outlet L _{WA6}	dB(A)	74	73	74	74	75
SPL casing break out L _{WA2}	dB(A)	60	59	59	58	58

Sound power (L _W) dB(A)		Medium Frequency Band								
		Σ	63	125	250	500	1k	2k	4k	8k
Inlet	L _{WA5}	73	34	44	63	67	67	68	63	59
Outlet	L _{WA6}	76	38	48	66	68	71	68	66	60
Casing	L _{WA2}	59	37	34	51	50	53	54	45	37

EM 200 E2M 01 127249	
Voltage U _N	230 V 1~
Current I _{max}	0,6
Ambient Temperature t _A	60 °C
Medium temperatures t _M	60 °C
Speed Control	3-2-1
Motor Protection	TAI
Isolation Class	F
Weight	3,8 kg

