

ACV 系列冷凝器

ACV SERIES AIR COOLED CONDENSER


ACV type, copper pipe铜管尺寸:3/8"OD, fin space片距:2.7mm,Hydrophilic aluminium亲水铝箔

Model 型号	Capacity KW 冷量 ($\Delta T=15^{\circ}\text{C}$)	Area 面积 m^2	Tube volume 管容 dm^3	Fan外转子风机				Connection pipe 接口尺寸		Overall(mm)外形尺寸			Install size(mm) 安装尺寸	
				Input 输入 功率 (w)	OD 外径 (mm)	Air flow 风量 (m^3/h)	Voltage 电压 (v)	Inlet 入	Outlet 出	L	W	H	A	B
ACV 2630 A93	93.0	138.4	24.2	2*800	630	24300	380	1-5/8"	1-1/8"	2192	342	1173	2038	188
ACV 2630 B104	104.0	189.2	30.3	2*800	630	24300	380	1-5/8"	1-1/8"	2192	342	1173	2038	188
ACV 3630 A130	129.3	196.6	32.7	3*800	630	36450	380	1-5/8"	1-1/8"	2792	342	1173	2638	188
ACV 3630 B150	150.8	277.8	44.4	3*800	630	36450	380	1-5/8"	1-1/8"	2792	342	1323	2638	188

Condensing temperature 40°C , ambient temperature 25°C , $\Delta T=15^{\circ}\text{C}$, R404A
冷凝温度 40°C 环境温度 25°C , 温差 15°C , R404a.

Correction factors修正系数:

Refrigerant 制冷剂	R404A	R134A	R22	R407C
	1	0.93	0.96	0.87



FNV 系列冷凝器

FNV SERIES AIR COOLED CONDENSER

FNV type, copper pipe铜管尺寸:3/8"OD, fin space片距:2.4mm

Model 型号	Capacity 冷量 Kw	Area 面积 m^2	Tube volume 管容 dm^3	Fan外转子风机				Connection pipe 接口尺寸		Overall(mm) 外形尺寸			Install size(mm) 安装尺寸	
				Input 输入 功率 (w)	OD 外径 (mm)	Air flow 风量 (m^3/h)	Voltage 电压 (v)	Inlet 入	Outlet 出	L	W	H	A	B
FNV-140	72.89	140	21.2	2×600	550	17000	380	2*7/8"	2*5/8"	1455	976	952	1330	896
FNV-175	103.50	175	29.6	2×800	630	24300	380	2*1-1/8"	2*7/8"	1755	1050	970	1630	970
FNV-195	117.77	195	29.6	2×800	630	24300	380	2*1-1/8"	2*7/8"	1755	1050	970	1630	970
FNV-260	146.89	260	44.3	3×800	630	36450	380	2*1-1/8"	2*7/8"	2555	1050	970	2430	970
FNV-295	162.33	295	44.3	3×800	630	36450	380	2*1-1/8"	2*7/8"	2555	1050	970	2430	970
FNV-365	195.85	365	55.4	3×800	630	36450	380	2*1-1/8"	2*7/8"	2555	1050	970	2430	970
FNV-405	223.56	405	61.2	4×800	630	48600	380	2*1-3/8"	2*1-1/8"	3155	1112	1032	3030	1032
FNV-505	267.39	505	76.5	4×800	630	48600	380	2*1-3/8"	2*1-1/8"	3155	1112	1032	3030	1032

Condensing temperature 40°C , ambient temperature 25°C , $\Delta T=15^{\circ}\text{C}$, R404A
冷凝温度 40°C 环境温度 25°C , 温差 15°C , R404a.

Correction factors修正系数:

Refrigerant 制冷剂	R404A	R134A	R22	R407C
	1	0.93	0.96	0.87

